

# ❖ 10.4" Touch Screen CIJ

## A Perfect Combination of Performance & Operation

- More stable and reliable with 32 bits Atmel industrial processor
- Easy interaction based on Linux platform
- Convenient to realize on-line print and upgrade
- Combination printing of messages in any order
- Sufficient store room for text messages with 64M memory space
- Innovative ink system has been granted the national patent



## Printer features

### Appearance

- 10.4 inches color touch screen with stainless steel enclosure
- Modular design for easy maintenance
- Automatic on-line monitor with various indication

### Message editing and printing

- Logo and graphics drawing easily on the screen
- Various and customized fonts available
- Editing and attribute modification for any field of information
- Data backup and restore functions to realize data exchange between printers
- Standard text and picture format for convenient data transmission with computer
- Variable text printing and random code stored for security printing

### System performance

- Multi languages interface and easy to switch
- Simple and clear interface for easy operation
- Log management to record real-time operation
- Timing shutdown, automatic flushing and convenient maintenance
- Anti-static and interference design to ensure a stable operation in complex environment

# Printing feature

<b>Model</b>	KN3430 / KN3430 <sup>+</sup>	
<b>Printing Lines</b>	1-3 lines	- 1-4 lines
<b>Fonts</b>	5x5,7x5,7x7,10x7,12x12,16x16,24x24	
<b>Printing Speed</b>	1076 charaters/s	
<b>Direction</b>	Inverse, reverse, mirror printing	
<b>Message Height</b>	1.8-5mm (7x5single line), 5-15mm (16x16single line)	
<b>Throw Distance</b>	2-15mm (standard),2-40mm (high quality)	
<b>Bold</b>	Up to 9 times	
<b>Language</b>	Chinese, English, Japanese, Korea, Thai, Vietnamese, Russian	
<b>Input Method</b>	English, Chinese, Wubi and Chinese phoneticize, Unicode charaters	
<b>Data Transmission</b>	Serial Port, Ethernet Port, USB Port	
<b>Memory Space</b>	64MB, Store over 10,000 text messages	
<b>Screen Size</b>	10.4 inches, 800x600 Resolution	
<b>Dimentions</b>	400x300x545mm	
<b>Net Weight</b>	26Kg	
<b>Operating Temperature</b>	5-45℃	
<b>Humidity Range</b>	30-95%RH (non-condensing)	
<b>Rated Voltage</b>	100-240V AC 50-60Hz	
<b>Rated Curent</b>	3A	

## 主界面



### Matthews Marking Products

USA: 6515 Penn Avenue, Pittsburgh, PA 15206

SWEDEN: Matthews Swedot AB  
Möbelgatan 4431 33, Mölndal, Sweden

CHINA Kenuohua Matthews Electronic Technology (Beijing) Company, Ltd  
Building C, Jinri Science Park No. 26 Jinyuan Road, Daxing Industrial Development Zone, Beijing

Tel: (412) 665-2500 Fax: (412) 365-2042

Tel: 46 31 338 7900 Fax: 46 31 845117

Tel: 86 10 88796525 Fax: 86 10 88796526